



TOP-HUNG WINDOW

OKPOL®
ROOF WINDOWS

ISKV I2

$U_w = 0,91 \text{ W/m}^2\text{K}^*$

GLAZING UNIT

$U_g = 0,5 \text{ W/m}^2\text{K}$

10 YEAR
GUARANTEE
FOR WINDOWS**

5 YEAR
GUARANTEE
FOR GLASS**



3-glazed window

gas - Krypto
2x warm spacer
2x low emission coat
toughened pane



4TH/12/4/12/4T

4 seals



safe handle with a lock and micro-opening function (2 keys included)



NEO - VENT air inlet allowing the inflow of fresh air



energy-saving window with a profile made of high-quality, glued pine wood, painted 3 times



installation angle



Sizes:

Glazing area [m2]	01	02	03	04	15	05	06	07	13	08	09	14	10	11	12
Symbol size	0.20	0.27	0.36	0.45	0.55	0.45	0.56	0.70	0.81	0.71	0.89	1.04	0.91	1.12	0.88
Window sizes: width x height [cm]	55x78	55x98	66x98	66x118	66x140	78x98	78x118	78x140	78x160	94x118	94x140	94x160	114x118	114x140	134x98
ISKV I2		✓	✓	✓	✓	✓	✓	✓		✓			✓		
Sash opening angle ISKV I2		57°	57°	59°	62°	57°	59°	62°		59°			59°		

* U_w - the thermal transmittance coefficient of the windows for reference sizes 1,23 (±25%)m x 1,48 (-25%)m, according to norm EN ISO 10077-1 / EN ISO 10077-2.

**Guarantee conditions are available at www.okpol.com.