

# WOODEN SKYLIGHT


INTEGRATED WITH FLASHING EPDM



# WVR V6

## 47 x 73

FOR NON HABITABLE AREAS



### TILE SUPPORT WEDGE

correct and aesthetic assembly of the roof



### BUTYL ON THE APRON'S INNER SURFACE

ensures exact fit of the apron



### SASH CLOSING LIMITER

at the full opening 90°



### THE HANDLE FOR OPENING SASH

3-stepped air access adjustment



### THE CHIMNEY-SWEEP RAIL

metal shield protects bottom part of the frame



### THE DRAINAGE GUTTER

drainage of condensate from the vapor barrier membrane



### ALUMINUM MESH IN THE LOWER PART OF THE FLASHING

perfectly fits to the roofing material



### DOUBLE GLAZING PACKET V6 WITH EXTERNAL TOUGHENED PANE

toughened glass is a hail resistant 4H/16/4(AR)



### FOR INSTALLATION IN THE ROOF PITCH 15° - 75°



### THE INTEGRATED FLASHING

made with EPDM



JOINERY IS MADE FROM IMPREGNATED AND GLUED PINE WOOD that extends of product lifetime



### COLOUR RAL 7016



### INTERCHANGEABLE SASH OPENING DIRECTION

from right to left side



### POSSIBILITY OF COMBINED HORIZONTAL INSTALLATION

joining any number of skylight(at a distance of 12cm)can be horizontally combined fit to the roof materials



### Sizes of skylight:

WVR V6 - 47 x 73 cm

**OKPOL®**

OKPOL 05.2024